











YOUR PRUDENT PARTNERS IN ALL KIND OF PACKAGING MACHINERY

We are one of the leading Innovative manufactures and exporters of Automatic Pouch Packing Machines. We manufacture world class packing machines in INDIA at very competitive price.





AFFS PACKING MACHINE POWDER / GRANULES

Filling Range Sealing Type	: Upto 200 g : Center, Three, Four Side Seal
Packing Speed	: 25-35 Pouch Per Minute (Depend on product)
Power Load	: 1.5 KW, 1Phase
Air Consumption	: 6.0 Kg/Sg.cm

All contact parts of food grade stainless steel Mechanical/ Pneumatic based model low maintain machine

PNEUMATIC AUGER CHUTE PACKING MACHINE POWDER

Filling Range	: Up to 1Kg	
Sealing Type	: Center, Three & Four Side Seal	
Packing Speed	: 15-50 Pouch Per Minute (Depend on product)	
Power Load	: 2.5 KW, 1Phase	
Air Consumption : 6.0 Kg/Sg.cm		

All contact parts of food grade stainless steel Servo/ Mechanical/Pneumatic based model low maintain machine





COLLAR TYPE VOLUMETRIC PACKING MACHINE POWDER / GRAINS / PULSES / SUGAR / RICE / DETERGENT POWDER

Filling Range	: Up to 5 Kg
Sealing Type	: Center Seal Pillow Type
Pouch Size	: L-50-320 mm, W-60-220 mm
Packing Speed	: 20-70 Pouch Per Minute (Depend on product)
Dimension	: 4000 x 970 x 60 mm
Power Load	: 3 KW,3 Phase
Air Consumption	: 6.0 Kg/Sg.cm

All contact parts of food grade stainless steel Servo/ Mechanical/Pneumatic based model low maintain machine



SERVO AUGER FILLER COLLAR TYPE PACKING MACHINE POWDER PACKAGING MACHINE

Filling Range	: upto 10 Kg
Sealing Type	: Center Seal Pillow Type
Pouch Size	: L-50-320 mm,W-60-220 mm
Packing Speed	: 20-70 Pouch Per Minute (Depend on product)
Dimension	: 14000 x 970 x 1160 mm
Power Load	: 5 KW, 3 Phase
Air Consumption	: 6.0 Kg/Sg.cm

All contact parts of food grade stainless steel Servo/ Mechanical/ Pneumatic based model low maintain machine



HMI & PLC	Seimens / Delta Make
Servo Drive	Seimens / Delta Make
Temperature Controller	SELEC / Multispan
Geared Motor	ABB / Transtech / Cromnton
A.C. Drive	Seimens / Delta Make
Photocell	Multispan / Panasonic
Sensor	SCH / IDEAL
Pneumatic	FESTO / SMC / JANATICS
Contact parts	Stainless steel 304 Food Grade
	Infeed Screw Elevator/Bucket elevator with base
	hopper and level sensor (optional)
	Pouch take off conveyor (optional)
	Date coding unit (Optional)



MULTIHEAD COLLAR TYPE PACKING MACHINE SNACKS / CHIPS / GRANULES

Filling Range	: Up to 10 Kg
Sealing Type	: Center Seal Pillow Type
Pouch Size	: L-50-320 mm, W-60-220 mm
Packing Speed	: 40-70 Pouch Per Minute (Depend on
product	
Dimension	: 14000 x 970 x 1160 mm
Power Load	: 5 KW, 3 Phase
Air Consumption	: 6.0 Kg/Sg.cm
Potato Chips, Kurku	ure, Macroni, Indian Namkeen, Puffed Snacks, Dry Fruits,
Nuts, Candies, Seed	ds, Soya Chunks, Breakfast Chunks, Breakfast Cereals, High
Counts Biscuits, Pas	ta, Whole Spices
	Pouch Size Packing Speed product Dimension Power Load Air Consumption Potato Chips, Kurke Nuts, Candies, Seed





EDIBLE OIL PACKING MACHINE FOR OIL PACKAGING

(Mechanical type, PLC based with touch screen, center seal/side seal)

Capacity : 200 ml to 1000 ml

: 4Kw

: 20 to 30 pouches per minute

: 415 V AC, 50 HHZ, 3 Phase

ELECTRICAL REQUIREMENT

Input Supply Connected Load

Speed

APPLICATIONS

Edible oil , ghee, vanaspathi, lubrication oils, paint and varnishes, fruit pulps, etc..

FEATURES

Fully automatic machines incorporated with PLC and touch screen. Contact parts are made of food grade materials Motorised film carrier adjustment, Motorised film roll unwinding system, Quantity can be adjusted with atmost easiness, Higher accuracy and higher consistency, Operator friendly

MILK PACKING MACHINE MILK POUCH PACKING MACHINE

(Mechanical type, PLC based with touch screen, Center seal/side seal)

Capacity : 200 ml to 1000 ml

Speed : 30 to 40 pouches per minute

ELECTRICAL REQUIREMENT

Input Supply : 415 V AC,50 HHZ, 1 & 3 Phase Connected Load : 4Kw

APPLICATIONS

Milk, Butter Milk, Curd, Flavored Milk, Lessi etc..


FEATURES

Fully automatic machines incorporated with PLC and touch screen. Contact parts are made of food grade materials Motorised film carrier adjustment, Motorised film roll unwinding system, Quantity can be adjusted with atmost easiness, Higher accuracy and higher consistency, Operator friendly





SIP UP / LOLLY / PEPSI PACKING MACHINE WATER / JUICE / FLAVORED MILK



Filling Range	: up to 100 ml
Sealing Type	: Center & Side Seal
Packing Film	: Laminated & LDPE
Packing Speed	: 25-35 Pouch Per Minute (Depend on product)
Power Load	: I KW, I Phase

All contact parts of food grade stainless steel Mechanical/ Pneumatic based model low maintain machine

FFS LIQUID PACKING MACHINE DETERGENT LIDUID / CAR WASH / SHAMPOO / KETCHUP

Filling Range	: up to 50 ml
Sealing Type	: Center, Three, Four Side Seal
Packing Speed	: 25-35 Pouch Per Minute (Depend on product)
Power Load	: I KW, IPhase



All contact parts of food grade stainless steel Mechanical/ Pneumatic based model low maintain machine



: Individual (Automatic)

CHIKKIES / CHOCOLATE / BISCUIT / SOAP / APPALAM

HORIZONTAL FLOW WRAP MACHINES

- : Center Seal Pillow Type : W-50 mm max., L-220 mm
 - : 40-100 Pouch Per Minute
 - : 3200 x 1525 x 1830 mm
 - : 3 KW. | Phase

Chikkies, Biscuits, Wafers, Cake, Soap, Ice Candy, Appalam Green & Steel Scrubbers and dummy products. Advantage of automation equipped with CE marked PLC Controller and touch screen HMI, Servo, Print mark scanners.





LINEAR WEIGHER PACKING MACHINE
GRANULES / NAMKEEN / CHIPS

Filling Range
Automation Grade
Voltage
Phase
Frequency
Capacity
Body Material
Motor Power
Filling System

- : 10 gm 1kg : Automatic : 220-240 V : Single Phase : 50 Hz : 40-50 Packets/Minute : Stain Less Steel : 1Hp
 - : 2,4,6 Head weigh Filler

Type of Sealing	: Center Seal, Three Side Seal, Four Side Seal.
Film Size	: 100mm-450mm width x 100mm-200mm length]
Film Roll Type	: Laminated Film in Roll Supported Film E.g. Polyester Film

COLLAR TYPE LINEAR WEIGHER PACKING MACHINE SUGAR, RICE , PULSES, GRAINS, TEA etc.

Minimum Order Quantity	: I Unit
Brand	: elitepacktech
Capacity	: 20-1000 gms
Sealing Type	: Center sealing/ Pillow type sealing
Packing Material	: Any heat sealable laminated film
Model Number	
Compressed Air Required	: 5 CFM@5 Bar
Electrical Power Required	:3 KW,420 V,3- Phase

Coller type PLC base machine suitable for free flowing products like Sugar, Rice , Pulses, Grains, Tea , Namkeen, Powder, Dry-Fruits, Seeds, Farsan, Potato chips, Frozen cut vegetables etc.

Machine can be easily synchronized with any one the following fillers to pack any kind of products.





FULLY AUTOMATIC BOTTLE PACKING UNIT

Automation Grade

Power

Speed

Applications

: 30-60 BPM : Filling, Capping, Induction Sealing Labeling, Batch Coding

: Fully Automatic

: 1.5 KW

FEATURES

Filling and Packaging systems for the Water, Carbonated Soft Drinks, Fruit Juices, Beer, Milk, Cosmetics, Lubricants & Pharmaceutical Industries.



AUTOMATIC WEB SEALER WITH SHRINK TUNNEL WATER / JUICE BOTTLES

- High speed Aero-Dynamic Blower Design
- Infra Red Ceramic Glass Heaters for Instant Heating.
- Digital temp. meter with auto cut sensor for highly accuracy constant heat in tunnel.
- AC drive with variable speed.
- Dual Mechanical Air Velocity Control.
- Stainless Steel Chain Conveyor.
- Works with contraction film of Multiple specification such as POF, PVC, PP, LDPE, CS & All shrink film.
- Sleeve wrapping Machines, Suitable for wrapping LDPE film around product and then Shrinking the packed products Like Bottles, Cans, Carton Boxes etc..





SEMI AUTOMATIC LIQUID & PASTE FILLING MACHINE LIQUID / PASTE / PICKLE / BATTER



- Automation Grade Filing Type Speed Usage/Application Machine Power
- : Semi-Automatic
- : Pneumatic
- : 10 15 Fillings / Min.
- : Liquid, Paste, Pickle, Batter
- :0-IHP

MULTI-TRACK PACKING MACHINE KETCHUP / OIL / SHAMPOO / POWDER / TEA

Machine Speed	: Upto 70/65/60 SPSm (According Product)	
Packaging Range	: I mm to 30 ml/gm	
No. of Tracks	: Depending on the pouch width (8-10)	
Max Roll Dia	: 800 mm/ 600 mm / 400 mm	
Max Length of Pouch	: Programmable 250 mm 150 mm	
Compressed Air	: 2 CFM @ 6 Kg I cm sq	
Electric Power	: 9.4 Kw I 7.6 Kw I 5.0 Kw	
Machine Dimension : 3950 x 1650 x 2600 (LxWxH)		
Net Weight	: 2200 Kg	



All contact parts of food grade stainless steel based model low maintain machine



BAND SEALER PACKING MACHINE

Automation Grade	: Semi-Automatic
Operational Mode	: Horizontal / Vertical
Model	: CBP-CBS
Voltage	: 220 V/50 Hz
Power	: 500 W
Sealing speed	: 0-12 m/min
Sealing width	: 6-12 mm
Temperature range	: 0-300 C
Max. conveyor loading	: 3 kg
Printing category	: Steel wheel printing
Weight	: 30 kg
Size	: 860x420x365 mm
Features:	



This series sealer is in the function on continuous carry, seal and print in one operation, and enable to horizontally, vertically and with stand, the machine adopts electronic constant temperature mechanism and step less speed adopts electronic constant temperature mechanism and step less speed adjusts transmission mechanism, it can seal plastic film in various kinds of materials



SEMI WEIGHER PACKING MACHINE GRANULES/POWDER

Minimum Order Quantity	: Piece
Filing Type	: Semi automatic
Sealing Type	: Semi-automatic
Usage/Application	: Powder/granules
Capacity	: 0-500 pouch per hour
Automation Grade	: Semi-Automatic
Pouch Capacity	: 10-1000 grams
Pouch Length	: all length
Machine Power	: 0-1 HP

Compact design , fast weighing system, Digital touch screen panel stainless steel parts, Flexible pouch holder for different size of pouch Foot operated mechanism, Wide packing range in single compact machine, Machine speed depend upon flow of material,



MIXTURE & PULVERIZER MACHINE



Capacity: 50 Kg to 500 Kg. per hour

Spices, Atta (Flour Products), Milk Powder, Nutraceuticals, Coffee Powder, Premixes, Instant Mixes, Agro Chemicals, Pesticides, Tobacco

AUTOMATIC & SEMI AUTOMATIC INDUCTION SEALING MACHINE

FEATURES

- Simple in Operation, air cooled
- Convenient torch unit for Max. output
- Works in the principle fo electro magnetic induction
- Ideal equipment for small production
- Induction Sealers Are Used For Hermetically Sealing The Plastic
 & Glass Bottle Caps With Aluminum Foils
- This Makes The Bottles Leakproof & Temper Evident And Offers Extended Shelf Live Used In Pharmaceutical Chemical. Lubricant, Cosmetic and Food Industries.







ASEPTIC BOX PACKING

FIRST GENERATION MACHINE

The 1st generation of brick box filling machine is used for mixing drinks and filling with additives of drinks, it belongs to the acid filling, no special requirements for sterilization system, the price of this machine relatively favourable, running stability, with many of patent design Inside of the machine . It is a good choice for mix of beverage factories.



SECOND GENERATION MACHINE

The new technology we have now, it is aseptic filling machines. This series of machine can fill pure juice and dairy milk. The machine has high technology in Aseptic chamber to ensure aseptic air as well as keeping positive pressure and hydro peroxide sterilization to packages materials. In this case, provide a complete aseptic filling environment plus high qualified sealed UHT and Mixing tank systems, the final products are wonderful and admirable with consumers. It is easy to operate by skilled workers and easy to repair it any. But the machine is not easy to broke and anything else because of proven technique.





ELITEPACKGROUP



Admn. Office : Elite Pack Group, D.No. : 28, Rani Garden, 5th Street, Aerodrome Road, Singanallur South, Coimbatore - 641005

Factory 1 : Elite Packtech, 304-D, Ramaswaminaudu Industrial Estate, Singanallur, Coimbatore - 641005

Factory 2 : Elite Packtech, 11/607, Chemmanthode, Nelliyampathi Road, Nemmara, Palakkad, Kerala - 678508

Bangalore Office : #1207/343 & 1207/1/343/1, 9th Main, 7th Sector, Hsr Layout, Bangalore, Karnataka 560102

Gujarat Office : 12, Gajanand Industrial Hub-3, Opp Hanuman Temple, Ramol-Hathijan Road, Vatva, Ahmedabad, Gujarat 382440

E mail : sales@elitepacktech.com

Website : elitepacktech.com

CALL FOR ENQUIRY :

Kerala : **+91 80899 99488** Karnataka : **+91 80899 92018** Tamil Nadu : **+91 79040 44552** Gujarat : **+91 70696 02306**

The Pouches shown in photographs are meant to indicate applications of machine. All pouches are not necessarily made by our customers. Due to continous R&D and up-gradation: appearence and specification of machines are subject to change without notice. The accessories in the picture may not be a part of standard equipment.